

SPECIFICATIONS

Property No. 259926

Defoamer

The defoamer is to be used to reduce foaming which occurs in the rug shampooing operation by the Industrial Cleaning Section.

The defoamer is used with the dry foam carpet shampoo cleaner (Property No. 219894) to maintain low foaming action from the cleaner which is used in Carpetron #18 Shampoo Machine manufactured by the Advance Floor Machine Co. The Shampoo Machine is a drum brush machine, (not a rotary disc machine).

One to three ounces of the defoamer is placed in the recovery tank of the shampoo machine to maintain a low suds level in the recovered foam. One of the active ingredients shall be silicone.

Specific Characteristics

Non-volatilize @ 120 C for 18 hours.....11.0% minimum
% Ash..... 1.5%

Packaging

The items shall be packaged in one-gallon plastic containers with a 1-1/4" (32mm) minimum screwtop cap and handle for easy pouring.

$$\text{Price per gallon of use dilution solution} = \frac{A \times B}{C}$$

Where A = bid price per contain of product
B = ounces of product needed to make one gallon of use dilution solution
C = ounces of product per container

Bidders shall state on their bid the amount of product (in ounces) required to make one gallon of use dilution solution as stated on the label. Where more than one use dilution solution is stated on the label, the sue dilution with the largest quantity of product per gallon of use dilution solution shall be used in determining the cost.

Sample Requirement

A one-gallon sample is required. Once the product is accepted, the supplier need no longer send in a sample unless the formulation is changed or he is offering a new product.

Qualified Product

Daycon Carpet Defoamer from Daycon products, Inc. complies with these specifications.